



### **Superior picture quality,** superb colour performance

The all-in-one display employs flip-chip COB technology, saving energy while being gentle on the eyes. With DCI-P3 wide colour gamut and 1000000: 1 contrast ratio, it delivers seamless colour transitions and reproduces every detail.

DCI-P3 Colour Gamut 1000

**1000000**: **1** Contrast Ratio







## **High-precision touch control,** inspiration at your fingertips

Supports touch control (compatible with dual systems) using highly precise infrared touch technology. Touch accuracy of  $\pm 2$ mm ensures flexible and accurate interactive operations, enabling natural and smooth writing for more convenient and efficient meetings.

### Versatile screen mirroring.

#### **Built-in professional meeting software.**

- ➤ Supports wireless screen mirroring for multiple platforms such as Windows, Mac OS, iOS, and Android, displaying up to four screens simultaneously.
- Comes with a meeting whiteboard, video conference and other software, and users can install additional apps as needed.

# ns and the second secon

## Multiple display modes, adaptive for all scenarios

Tailored for different meeting environments, offering Standard, Soft, Cinema, and Video modes for optimal display in any setting.



15%

### Flexible installation, easy maintenance

- > Full front maintenance design allows for convenient installation and service.

> Support wall mounting and mobile stand-mounting.

### **SPECIFICATIONS**

Model	S108COBVB-FSN	SR108COBVB-FSN	S135COBVB-FSN	SR135COBVB-FSN	S163COBVB-FSN	SR163COBVB-FSN	S216COBVB-FSN
Display Size	108"	108"	135"	135"	163"	163"	216"
Resolution	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	3840*2160
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Touch control	No	Infrared touch	No	Infrared touch	No	Infrared touch	No
Overal Dimensions (W x H x D mm)	2410 x 1480 x 31 Bottom Thickness 47mm	2423 x 1487 x 45 Bottom Thickness 47mm	3010 x 1817.5 x 31 Bottom Thickness 47mm	3023 x 1824 x 45 Bottom Thickness 47mm	3610 x 2155 x 31 Bottom Thickness 47mm	3623 x 2161 x 45 Bottom Thickness 47mm	4810 x 2830 x 31 Bottom Thickness 47mm
Actual Screen Dimensions (W x H mm)	2400 x 1350mm	2400 x 1350mm	3000 x 1687.5mm	3000 x 1687.5mm	3600 x 2025mm	3600 x 2025mm	4800 x 2700mm
Installation Method	Mobile Stand/Wall Mounting						Wall Mounting
Refresh Rate(Hz)	3840						
Brightness(nits)	600						
Gray Scale(Bit)	22						
Contrast Ratio	1000000:1						
Viewing Angle(H./V.)	160°/160°						
Maintenance Method				Front			
Operating System	Android 11.0, 4+32G						
Working Voltage	AC:100V~240V, 50/60Hz						
Power Consumption Max(W)	1200	1200	1850	1850	2450	2450	4600
Power Consumption AVG(W)	400	400	620	620	820	820	1550
Storage Temp(°C)	-20 ~ 60						
Operating Temp(°C)				-10 ~ 50			
Storage Humidity (%RH)				10 ~ 90			
Operating humidity (%RH)				10 ~ 80			

